

Simple to use. Hooks up to a 12 volt battery.

- When used in water, all pumps are rated for continuous use. No need for a cool down!
- All Pumps can run dry for up to 2 hours without motor damage!
- All pumps are auto-primed.
- All Pumps fit into a 2" well (Except the Abyss Pump).
- All Pumps are rated for over 400 hours of use when used in water.
- All pumps can be used in harsh conditions with higher turbidity.**

All 1.82" O.D. Engineered Plastic Pumps now feature a domed top and bottom. *

Domed top minimizes well hang ups.

Fits 3/8" ID polyethylene tubing.

Reinforced, super strong discharge outlet (durable, field-tested).

Fits 1/2" ID polyethylene tubing.

Computer engineered domed bottom debris Screen will separate Debris from water, thus extending motor life.

Non-Return (Non Vented) Check Valve

Top-fitting accessory used to prevent water back-flow when technician shuts off pump. Ideal for Low Flow Sampling.

Used With Standard and High Performance Engineered Plastic Pumps.

Item #PA-15020

Accessory Item



*Excludes the Abyss Pump
Specifications subject to change without notice.

**Pump technique is common sense, don't use our pumps as a vacuum cleaner.

MEGA-MONSOON

**IMPROVED DESIGN!
MORE COMPACT,
SAME POWER!**



Item No. P-10520

PUMPING DEPTH: 200ft. DTW* (61 Meters)

- Supplied with 210 feet of heavy duty 10 gauge wire.
- Dimensions: 1.82" O.D.x26" Length.
- Requires: Low Flow with Power Booster 3 (PA-10850).
- High Impact Plastic Reel Included.
- Can be used with 3/8" or 1/2" ID Low Density Polyethylene Tubing.

DTW Means Depth-To-Water. Specifications subject to change without notice.